

CLAIMS

What is claimed is:

1. Control device for a bicycle, comprising:
a first body adapted to be associated with a bicycle handlebar;
at least one control member that controls at least one bicycle component that is remote from the control member; and
a second body that is distinct from the first body,
wherein the first body defines a grip portion of the control device and the second body defines at least one of: a further grip portion of the control device, and a portion that changes the position of the first body relative to the bicycle handlebar.
2. Device according to claim 1, wherein the first body defines a first grip portion of the control device and the second body defines a second grip portion of the control device and is associated with the first body to vary the distance of the at least one control member from the handlebar.
3. Device according to claim 1, wherein the second body is associated with the first body at respective coupling surfaces having a matching shape.
4. Device according to claim 1, wherein the second body is positioned in a single predetermined position with respect to the first body.
5. Device according to claim 4, wherein the second body is associated with the first body through screws.
6. Device according to claim 4, wherein the second body is associated with the first body through glue.

7. Device according to claim 4, wherein the second body is associated with the first body through a snap coupling.
8. Device according to claim 1, further comprising at least one adjustment member for adjusting the position of the second body with respect to the first body.
9. Device according to claim 8, wherein the at least one adjustment member comprises a screw/female screw coupling operatively arranged between the first body and the second body.
10. Device according to claim 9, wherein one from the screw and the female screw is associated with one from the first body and second body and the other from the screw and the female screw is associated with the other from the first body and second body.
11. Device according to claim 1, wherein the second body is removably associated with the first body.
12. Device according to claim 1, further comprising an outer coating sheath which covers the first body and second body.
13. Device according to claim 1, wherein the second body is associated with a lower surface of the first body.
14. Device according to claim 13, wherein the control device further comprises a lower wall defined in part by the lower surface of the first body and in part by a lower surface of the second body.
15. Device according to claim 13, wherein the control device further comprises a lower wall defined integrally by a lower surface of the second body.

16. Device according to claim 1, wherein the second body is associated with an outer side surface of the first body.

17. Device according to claim 16, wherein the control device further comprises an outer side wall defined in part by the outer side surface of the first body and in part by an outer side surface of the second body.

18. Device according to claim 16, wherein the control device further comprises an outer side wall defined integrally by an outer side surface of the second body.

19. Device according to claim 1, wherein the second body is associated with an inner side surface of the first body.

20. Device according to claim 19, wherein the control device further comprises an inner side wall defined in part by the inner side surface of the first body and in part by an inner side surface of the second body.

21. Device according to claim 19, wherein the control device further comprises an inner side wall defined integrally by an inner side surface of the second body.

22. Device according to claim 1, wherein the second body is associated with an upper surface of the first body.

23. Device according to claim 22, wherein the control device further comprises an upper wall defined in part by the upper surface of the first body and in part by an upper surface of the second body.

24. Device according to claim 22, wherein the control device further comprises an upper wall defined integrally by an upper surface of the second body.
25. Device according to claim 1, wherein the second body is associated with a rear surface of the first body, so as to be operatively arranged between the first body and the handlebar when the first body is associated with the handlebar.
26. Device according to claim 25, wherein the control device comprises a rear wall defined in part by the rear surface of the first body and in part by a rear surface of the second body.
27. Device according to claim 25, wherein the control device comprises a rear wall defined integrally by a rear surface of the second body.
28. Device according to claim 1, wherein the second body, when associated with the first body, extends at least partially over at least one of a lower surface, an inner side surface, an outer side surface, an upper surface, and a rear surface of the first body.
29. Bicycle comprising a control device according to claim 1.
30. Kit of parts for the assembly of a control device for a bicycle, comprising a first body adapted to be associated with a bicycle handlebar and provided with at least one control member of at least one bicycle component, and at least two second bodies adapted to be selectively associated with the first body, wherein the at least two second bodies differ in at least one of shape and size.
31. A control device for a bicycle, the control device comprising:
 - a first body mounted to a bicycle handlebar;
 - at least one control member that controls a bicycle component; and

a second body associated with the first body,
wherein the first body defines a first grip portion of the control device,
wherein the second body varies a distance of the at least one control member
from the handlebar.

32. The control device according to claim 31, wherein the second body is associated with the first body at a lower surface of the first body and extends substantially over the entire lower surface of the first body.

33. The control device according to claim 32, wherein each of an outer side wall and an inner side part of the control device has a respective surface substantially parallel to a substantially vertical intermediate reference plane P that passes through the control device.

34. The control device according to claim 31, wherein the second body is associated with the first body at an inner side surface of the first body.

35. The control device according to claim 33, wherein an inner side wall of the control device has surface portions not parallel to a substantially vertical intermediate reference plane P that passes through the control device.

36. The control device according to claim 31, further comprising at least one adjustment member for adjusting the position of the second body with respect to the first body.

37. The control device according to claim 36, wherein the second body comprises a portion that projects rearwardly with respect to the first body.

38. The control device according to claim 37, wherein upon activation of the adjustment member, a grip surface of the control device 1 and the distance of the at least one control member from the handlebar are simultaneously adjusted.

39. Control device for a bicycle, comprising:

a first body adapted to be associated with a bicycle handlebar;

at least one control member that controls at least one bicycle component that is remote from the control member; and

a second body that is distinct from the first body,

wherein the first body defines a grip portion of the control device and the second body changes the position of the control member relative to the bicycle handlebar.

40. The control device of claim 39, wherein the second body changes the position of the control member relative to the bicycle handlebar by rotating the control member with respect to the handlebar.

41. The control device of claim 40, wherein the second body has a first portion that mates with the first body and a second portion that mates with the handlebar.

42. The control device of claim 41, wherein the second body mates with the first body in a snap engagement.