

IN THE CLAIMS

Each claim of the present application is set forth below with a parenthetical notation immediately following the claim number indicating the current claim status. The Examiner's entry of the claim amendments, as shown in marked-up form, under Section 1.116 is respectfully requested.

1. (canceled)

2. (canceled)

3. (canceled)

4. (currently amended) An ~~The~~ antenna of ~~claim 1~~ for placement in an opening within a first conductive material, the antenna comprising:

_____ a dielectric tubular member;

_____ a second conductive material forming an exterior surface of the tubular member;

_____ the second conductive material defining a slot therein, the slot having a slot length approximately equal to one-half of a guided wavelength and having a slot width, there being no slot present in the tubular member immediately beneath the slot in the second conductive material, wherein a width of the opening defined by the first conductive material is less than a quarter wavelength of the guided wavelength; and

_____ a feed proximate the slot for establishing currents in the second conductive material when the antenna is in a transmitting mode, the currents perpendicular to the slot length.

5. (original) A communications device for sending and receiving an information signal, the communications device comprising:

an element having an opening defined therein for receiving an antenna, the element comprising first conductive material disposed proximate the opening;

transmitting and receiving circuits;

the antenna comprising:

a dielectric tubular member;
second conductive material forming an exterior surface of the tubular member;
the second conductive material defining a slot therein, a slot length approximately equal to one-half of a guided wavelength; and
a feed connected to the transmitting and receiving circuits and disposed proximate the slot for establishing currents in the second conductive material when the antenna is in a transmitting mode.

6. (original) The device of claim 5 wherein the currents are perpendicular to the slot length.

7. (original) The device of claim 5 wherein the slot length is substantially greater than a slot width.

8. (original) The device of claim 5 wherein a dielectric constant of the dielectric tubular member is at least 10.

9. (original) The device of claim 5 wherein the antenna comprises a slotted cylinder antenna.

10. (original) The device of claim 5 wherein a width of the opening for receiving the antenna is less than a quarter wavelength at an operating frequency of the antenna.

11. (original) The device of claim 5 wherein the second conductive material further defines a gap therein, the gap extending a length of the tubular member.

12. (original) The device of claim 5 wherein a cross section of the tubular member comprises one of a D-shaped cross-section, a circular cross-section, a rectangular cross-section and a square cross-section.

13. (original) The device of claim 5 wherein the feed comprises a first conductor connected to the second conductive material and a second conductor extending across a width of the slot from a first edge of the slot to a second edge of the slot and connected to the second edge.

14. (original) The device of claim 5 wherein the element having an opening therein comprises a laptop computer screen or a laptop computer

keyboard, and wherein a radiation pattern is substantially omnidirectional relative to a long axis of the slot.

15. (original) The device of claim 5 wherein the antenna exhibits two closely spaced resonant frequencies.

16. (original) The device of claim 5 wherein the antenna comprises at least two slots each separately excited.

17. (original) The device of claim 5 wherein the two slots have a substantially equal resonant frequency and provide antenna diversity for the communications device.

18. (original) The device of claim 5 wherein the slot comprises a J-shaped slot.

19. (original) The device of claim 18 wherein the J-shaped slot comprises a short leg having a first resonant frequency and a long leg having a second resonant frequency.

20. (original) The device of claim 5 wherein the feed comprises a microstrip probe mounted proximate the slot.