

Amendments to the Specification

Please replace the heading on line 1 of page 1 of the specification as originally filed, in its entirety, with the following amended heading:

**Description** TITLE

Please replace the heading on line 3 of page 1, directly before paragraph [1] of the specification as originally filed, in its entirety, with the following amended heading:

**Technical Field** FIELD OF THE INVENTION

Please replace the heading on line 8 of page 1, between paragraphs [1] and [2] of the specification as originally filed, in its entirety, with the following amended heading:

**Background Art** BACKGROUND

Please replace the heading on lines 19-20 of page 3, between paragraphs [13] and [14] of the specification as originally filed, in its entirety, with the following amended heading:

**Disclosure of the Invention**

**Technical Problem** BRIEF SUMMARY OF THE INVENTION

Please remove the heading on lines 1 of page 4, between paragraphs [16] and [17] of the specification as originally filed, in its entirety as shown here:

**Technical Solution**

Please remove the heading on lines 9 of page 5, between paragraphs [24] and [25] of the specification as originally filed, in its entirety as shown here:

~~**Advantageous Effects**~~

Please replace the heading on line 25 of page 5, between paragraphs [27] and [28] of the specification as originally filed, in its entirety, with the following amended heading:

~~**Brief Description of the Drawings**~~ BRIEF DESCRIPTION OF THE DRAWINGS

Please replace the heading on line 15 of page 7, between paragraphs [74] and [75] of the specification as originally filed, in its entirety, with the following amended heading:

~~**Mode of the Invention**~~ DETAILED DESCRIPTION

Please replace paragraph [98], in its entirety, with the following amended paragraph:

[98] The vertical partition 20 of the dispenser body 10 is a plate member having a size and profile capable of dividing the inner space of the dispenser body 10 into two inner spaces, and is fixed using a support plate 300 [[27]] installed on the bottom plate 14. The support plate 300 [[17]] has two L-shaped plates spaced apart by a predetermined distance, and the lower end of the vertical partition 20 is inserted and fixed between the two L-shaped plates. At this time, the support plate 300 [[17]] and the vertical partition 20 are fastened using a plurality of fastening screws 301 [[28]].