

Search Terms

-
- reset
- ring-back
- UL grant
- timer
- protocol
- bit link
- down protocol
- subscriber station
- link up
- wireless communications
- timer
- mobile station
- ul allocation
- timeout

Custom Date Range

Start date:

End date:

PN9110 - Comcast

<http://media2.comcast.net/arc-on-comcastonline2/support/help/faq/settopboxes/pn9110...>
 Aug 24, 2009 - This manual describes some on-screen displays such as menus. left unattended and unused for long periods of time, disconnect the set-top your home theater receiver and the OPTICAL AUDIO OUT jack (as shown in the diagrams). Pace reserves all rights not expressly granted to you under these Terms. 3.

Determining RF or Configuration Issues on the CMTS - Cisco

<http://www.cisco.com/it/en/us/support/docs/cmts/cable/radio-frequency-rf-hybrid-fiber-Sep-3-2008> - It is unusual to have this quantity of traffic being passed and at the same time policy and derived from the initial cable network setup, relative to the analog ... with several hundred cable modems, they may take a long time to come back online. ... BW Requests= 0x0 Minislots Requested= 0xA52 Minislots Granted = 0xA52 ...

US5434847 - Google

<http://www.google.com/patents/US5434847>
 Jul 18, 1996 - The packet containing the count value is retransmitted on a time slot ... if an acknowledgment signal is received, the count value is reset to zero. ... by said traffic data, said random number generator being responsive to receipt of no The acknowledgment (ACK) field contains as many acknowledgment signals as there are ...

javascript - What's the best way to set cursor/caret position? - Stack ...

<http://stackoverflow.com/questions/1262302/whats-the-best-way-to-set-cursor-caret-position>
 Aug 6, 2009 - Somewhere near the end I discovered that this function works to restore the ... This does not place the caret after the last element if the last element is a ul or ol ... find the correct selector so that newNode is the element of your editor text mg. ... href="http://robubu.com">robubu.com); //horrible hack to put the cursor in ...

IEEE Standard 802.16 - GRC

<http://www.grc.upv.es/bitstream/local/IEEEStandard802.16.pdf>
 Jun 30, 2002 - at subscriber stations allocated time slots serial- ly. Access in the the UL-MAP grants bandwidth to specific SSs. The SSs transmit in reconstructed back into the original MAC SDUs so that the The SS can use the RNG-REQ message to request a change reset its perception of the SS's needs without a complicated ...

mFOAM-1.02: A Compact Version of the Cellular Event Generator ...

<http://arxiv.org/pdf/physics/0508054>
 Jun 9, 2005 - Institute of Nuclear Physics, Academy of Sciences, ul. Radzikowskiego 152, 31-342 ... *Supported in part by EU grant MTKD-CT-2004-510126, in partnership with ... The CPU time necessary to build up a foam of cells depends strongly on the Resets the pointer to r.n.g. in mFOAM we go back to the pointers, but instead.

IEEE Standard 802.16. A Technical Overview of the ... - IEEE 802

http://www.ieee802.org/16/docs/02/080216-02_05.pdf
 Jun 4, 2002 - (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE. at subscriber stations allocated time slots serial- ly. Access in reconstructed back into the original MAC SDUs so that the use the RNG-REQ message to request a change ... connection setup time.

Vienna LTE-A Simulators, Link Level Simulator ... - ResearchGate

<https://www.researchgate.net/file/PostFileLoader.htm?file=S4127174d11b1b15e311b5463e8ee...>
 Dec 25, 2008 - XVIII-C Grant of source code license RUNNING THE SIMULATOR FOR THE FIRST TIME ... are adapted in accordance with the channel quality experienced and fed back LTE_params.uplink_delay: the delay the uplink experiences. ... N_seed_reset: resets the random number generator seeds to a new value after ...

M54455EVB User's Manual - NXP

http://www.nxp.com/files/32bit/doc/user_guide/M54455EVBUM.pdf?srch=1
 Aug 25, 2007 - Programmable interrupt timers. PLL – Phase locked loop module. RNG – Random Number ... at, Re v. 4. F. Resealable Semiconductor. 6. Figure 3. M54455EVB Block Diagram. ColdFire ... Refer to Figure 4 for the I/O back panel descriptions. Figure 4. PCI Grant 0 Cut Trace Option—Use FPGA for Arbitration. Figure 10.

Application US2012002621



Air link up/down protocol (alu)

Show Claims

Inventors: Lei Wang, Ronald G. Nunes
 Assignees: Interdigital Patent Holdings, Inc
 Publication number: US2012002621
 Application number: 13/172,858